



A Tradition of Quality. Since 1905

DV-03 ALUMINUM DRY VAN

STANDARD SPECIFICATIONS

| | |
|----------------------------------|--|
| FLOOR | <ul style="list-style-type: none">• 4" I-beam stringers• 3" 60,000 psi I-beam crossmembers on 12" centers• 1-1/8" laminated hardwood floor - two 5/16" screws per board (staggered pattern), per crossmember• Undercoated |
| FRONT WALL AND SIDE WALLS | <ul style="list-style-type: none">• Aerodynamic extruded aluminum 5" radius front corner posts and front top radius• Extruded aluminum lower front rail, lower and upper side rails• Grote marker lights (69020000 and 69020100) with standard lenses• Reflectors per FMVSS• Seven (7) posts on front wall• Full width x 8" high steel reinforcement angle at base of front wall• Galvanized steel "Z" section side wall posts on 16" centers• "Smooth Side" construction - exterior surface of side and front wall panels are rivet-free• .040" prepainted white aluminum exterior panels |
| REAR FRAME AND DOOR | <ul style="list-style-type: none">• Rear corner posts and door frame formed of galvanized steel• 13" chrome access handle located at curbside rear• Roll-up rear door, 94" wide opening with top, bottom and side seals. Includes 30" pull strap• 4-1/4" smooth steel level entry with recessed drain trough - flooring end cap routed flush with top of floor. |
| ROOF | <ul style="list-style-type: none">• Aerodynamic cast aluminum front corner caps with gusseted design• Crowned rolled galvanized steel hat section rafters on 24" centers• .06" one piece translucent roof |
| MOUNTING | <ul style="list-style-type: none">• Mounted including frame wood, U bolts, mud flaps and DOT step |