



A Tradition of Quality. Since 1905

DV-FRP-03 DRY VAN

STANDARD SPECIFICATIONS

FLOOR	<ul style="list-style-type: none">• 4" I-beam stringers• 3" 60,000 psi I-beam crossmembers on 12" centers• 1-1/8" laminated hardwood floor - two 5/16" screws per board (staggered pattern), per crossmember• Undercoated
FRONT WALL AND SIDE WALLS	<ul style="list-style-type: none">• Aerodynamic extruded aluminum 5" radius front corner posts and front top radius• Extruded aluminum lower front rail, lower and upper side rails• Grote marker lights with standard lenses• Reflectors per FMVSS• 1/2" core color impregnated white FRP exterior panels• Upper and lower side and front rails of extruded aluminum
REAR FRAME AND DOOR	<ul style="list-style-type: none">• Rear corner posts and door frame formed of galvanized steel• Roll-up rear door, 94" wide opening with top, bottom and side seals. Includes 30" pull strap• 4-1/4" smooth steel level entry with recessed drain trough - flooring end cap routed flush with top of floor.• One access handle located at curbside rear of van
ROOF	<ul style="list-style-type: none">• Aerodynamic cast aluminum front corner caps with gusseted design• Crowned rolled galvanized steel hat section rafters on 24" centers• .06" one piece translucent roof
MOUNTING	<ul style="list-style-type: none">• Mounted including frame wood, U bolts, mud flaps and DOT step